

# Reasoning for the product

# LIQUI MOLY



## Wide range of applications

- rusted and seized screws
- patches of rust
- fixed nuts
- stiff hydraulics
- squeaking doors
- sluggish door locks
- locking mechanisms to be maintained on windows
- stubborn stains
- residues from stickers
- dirty tools
- oil slicks
- stubborn limescale
- soiled metal parts
- matt chrome parts on the car
- corroded poles of the car battery
- electrical plugs with contact problems
- and more

## The all-rounder LM 40

In many areas in industry, workshops and households, material-compatible products with particularly high penetration properties are required to maintain machines and equipment, keep metal parts running smoothly, improve electrical conductivity or protect against corrosion.

### Advantages of LM 40

LM 40 is a true all-rounder, combining five products in one:

#### Rust solvent

Thanks to an active ingredient content of 97 %, LM 40 has exceptionally high penetration properties and even infiltrates stubborn rust and dirt. This property enables the loosening of heavily rusted screws in the shortest time.

#### Lubricant

Lubricates without greasing. LM 40 does not contain any silicones and is neutral to paint, metal, wood and plastic (except polycarbonate/PMMA). It is characterized by excellent adhesion and particularly high penetration properties and is therefore also particularly suitable for hard-to-reach areas.

#### Cleaner

Infiltrates dirt, oil and greasy deposits. Removes tar, adhesive and residues from stickers.

#### Corrosion inhibitor

The tough film even protects metals that are subject to regular use. The excellent adhesion to metal prevents corrosion and oxidation by moisture even on uneven, easily attackable surfaces.

#### Contact spray

LM 40 forms a moisture-repellent protective layer on metal and infiltrates moisture. This improves the conductivity of electrical contacts and prevents oxidation.

Lubricates, cleans, loosens, protects and preserves.  
In industry, workshops and households.



Part no.	Product	Cont.	Language	PU
3394	LM 40 Multi-Purpose Spray	50 ml	D-GB	12
3390	LM 40 Multi-Purpose Spray	200 ml	D-GB-I-E-P	12
3391	LM 40 Multi-Purpose Spray	400 ml	D-GB-I-E-P	12

No liability for misprints. Subject to technical modifications.



With a pleasant  
**coconut fragrance**

LIQUI MOLY GmbH  
Jerg-Wieland-Straße 4  
89081 Ulm  
GERMANY

Phone: +49 731 1420-0  
Fax: +49 731 1420-75  
E-Mail: [info@liqui-moly.com](mailto:info@liqui-moly.com)  
[www.liqui-moly.com](http://www.liqui-moly.com)

Technical Support:  
Phone: +49 731 1420-871  
E-Mail: [support@liqui-moly.com](mailto:support@liqui-moly.com)

510951809