








Overview service products maintaining and lubricating



| | PTFE Longlife Spray | PTFE-Powder Spray | Tacky Lube Spray | Care and Lubricating Spray | Pro-Line Silicone Spray | Multi-Spray Plus 7 | LM-40 Multi-Purpose Spray |
|--|---|---|---|---|---|---|---|
| |  |  |  |  |  |  |  |
| Content | 400 ml | 400 ml | 400 ml | 400 ml | 400 ml | 300 ml | 50/200/400 ml |
| Part no. | 20971 | 3076 | 4084 | 20665 | 7389 | 3304 | 3394/3390/3391 |
| Lubricity under low load < 150 N | ● ● ● | ● | ● ● | ● ● | ● ● ● | ● ● | ● ● |
| Lubricity under high load > 150 N | ● ● ● | ● | ● ● ● | ● | ● | ● ● | ● |
| Rust solvent properties | ● | | | ● | | ● ● ● | ● ● ● |
| Adherence | ● ● ● | ● ● ● | ● ● ● | ● ● | ● ● ● | ● ● | ● ● |
| Corrosion protection | ● | | ● | ● | ● | ● ● ● | ● ● |
| Tendency to form stains (textile/plastic) | ● | | ● | ● ● ● | ● ● ● | ● ● | ● ● |
| Displacement of moisture | ● ● ● | | ● | ● ● | ● ● | ● ● ● | ● ● ● |
| Compatibility with paints | ● ● ● | ● ● ● | ● ● ● | ● ● ● | ● ● ● | ● ● ● | ● ● ● |
| Compatibility with plastic | ● ● | ● ● | ● ● | ● ● ● | ● ● ● | ● ● | ● ● |
| Insulating property/non-conductive | ● ● ● | ● ● ● | ● ● ● | ● ● ● | ● ● ● | ● ● ● | ● ● ● |
| Mineral oil basis | ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ |
| Silicone-free | ✓ | ✓ | ✓ | ✓ | | ✓ | ✓ |
| Operating temperature range in °C | -30 to +180, short term +200 | -40 to +250 | -30 to +180, short term +200 | -10 to +120 | -35 to +350 | -40 to +140 | -40 to +140 |
| Contains PTFE | ✓ | ✓ | | | | | |