

MEGUIN
OILS OF GERMANY

Products for cars

www.meguin.de

With best regards:

504911703

Meguin GmbH & Co KG
Mineraloelwerke
Rodener Straße 25
66740 Saarlouis
Germany
Telefon: +49 6831 89 09-0
Fax: +49 6831 89 09-59
E-Mail: vertrieb@meguin.de



megol Motorenoel New Engine FE SAE 5W-20

Engine oil based on HC synthesis technology with the latest additive technology that has been specially developed for Ford EcoBoost-motors. The lowviscosity reduces CO_2 content and the fuel consumption.

Specifications/Approvals:
ACEA A1
ACEA B1
API SN
Ford WSS-M2C 948-B
Jaguar / Land Rover STJLR.03.5004

Content	PU	Part-No.
5 l	4	9291
20 l	1	9293
60 l	1	9295
200 l	1	9297



megol Special Engine Oil SAE 5W-20

High performance engine oil based on HC synthesis technology with a new-generation additive system, which has been specially tailored to suit the requirements of American and Asian automotive manufacturers. megol Special Engine Oil SAE 5W-20 fulfils the highest performance requirements for modern petrol engines, ensures low wear, clean engine operation and long oil change intervals.

Specifications/Approvals:
API SN
ILSAC GF-5

Recommendations:
Chrysler MS-6395
Ford WSS-M2C 930-A, 945-A
GM 6094 M
Honda; Mazda
Mitsubishi Dia Queen
Nissan

Content	PU	Part-No.
1 l	12	9498
5 l	4	9499
60 l	1	7042
200 l	1	7072



megol Motorenoel Fuel Economy SAE 5W-30

High performance motor oil based on HC synthesis technology with a latest generation additive system (Low-SAPS Technology and reduced HTHS). For maximum fuel savings and efficiency. Meets the high performance requirements of modern gasoline and diesel engines and ensures maximum service life of the diesel particulate filter as well as low wear, clean engine operation and long oil change intervals.

Specifications/Approvals:
ACEA C2
API SN/CF
Mazda, Honda, Toyota

Recommendations:
ACEA A1/B1
ACEA A5/B5
Fiat 9.55535-S1
PSA B71 2290
Renault RN 0700

Content	PU	Part-No.
1 l	12	9440
5 l	4	9441
20 l	1	9442
60 l	1	9443
200 l	1	9444



megol Motorenoel Compatible SAE 5W-30

High-performance long life motor oil based on modern Low-SAPS Additive Technology and HC synthetic base oils offering a persuasive combination of outstanding properties. Can be used in VW vehicles with and without extended maintenance intervals (WIV), in FSI engines and diesel vehicles, incl. those with a diesel particulate filter (DPF) and turbocharger.

Specifications/Approvals:
ACEA C3
API SN
BMW Longlife-04
MB-Approval 229.51, 229.31
Porsche C30
VW 504 00/507 00

Recommendations:
ACEA A3/A5/B4/B5/C2; API CF; BMW Longlife-01/01 FE; Fiat 9.55535-S1; Peugeot Citroen (PSA) B71 2290; VW 500 00/501 01/502 00/503 00/503 01/505 00/505 01/506 00/506 01 (With the exception of R5 and V10 TDI engines before 6/2006)

Content	PU	Part-No.
1 l	12	6561
1 l	12	9619 [1]
5 l	4	6562
5 l	4	9621 [1]
20 l	1	6563
60 l	1	6564
200 l	1	6565
IBC 1000 l	1	9622



megol Motorenoel Quality SAE 5W-30

Modern multigrade low-friction motor oil of the latest generation. Suitable for year-round use. Its combination of unconventional HC base oils with the very latest additive technology guarantees low viscosity and high shear resistance. This product reliably prevents the formation of deposits, reduces frictional losses in the engine and optimally protects against wear. Ensures savings in fuel and an extended service life of the engine. Specially recommended for OPEL gasoline and diesel engines with no diesel particulate filter (DPF), including those with a turbocharger and catalytic converter.

Specifications/Approvals:
ACEA A3/B4
API SL/CF
BMW Longlife-01
MB-Approval 229.5
VW 502 00/505 00

Recommendations:
Opel GM–LL–A–025
Opel GM–LL–B–025
Renault RN 0700

Content	PU	Part-No.
1 l	12	6566
4 l	4	9027
5 l	4	6567
20 l	1	6568
60 l	1	6582
200 l	1	6687
IBC 1000 l	1	8497



megol Motorenoel New Generation SAE 5W-30

High performance motor oil based on HC synthesis technology with a latest generation additive system (Low-SAPS Technology). Complies with the high performance and quality requirements of modern gasoline and diesel engines. Ensures maximum service life and function of the diesel particulate filter (DPF) as well as low wear, clean engine operation and long oil change intervals alongside low fuel consumption.

Specifications/Approvals:
ACEA C3
API SN/CF
BMW Longlife-04
MB-Approval 229.51
VW 502 00/505 00

Recommendations:
ACEA A3/B4
dexos 2
Ford WSS-M2C 917-A
VW 505 01

Content	PU	Part-No.
1 l	12	6512
5 l	4	6513
20 l	1	6696
60 l	1	4609
200 l	1	6697



megol Motorenoel Mobility SAE 5W-30

High-performance motor oil based on the most recent low SAPS technology. Specially tailored to suit the requirements of modern exhaust aftertreatment systems. Developed especially for the latest generation of passenger car diesel engines from Renault. Ensures maximum service life of the diesel particulate filter as well as low wear, clean engine operation and long oil change intervals.

Specifications/Approvals:
ACEA C4
Renault RN 0720

Content	PU	Part-No.
1 l	12	3185
5 l	4	3182
20 l	1	9468
60 l	1	9469
200 l	1	9470

[1] GB-F-E-P-NL-ARAB



megol Motorenoel Ecology SAE 5W-30

High-grade engine oil based on the most recent low SAPS technology with reduced HTHS value, which has been specially tailored to suit the requirements of modern final exhaust gas treatment systems. megol Motorenoel Ecology SAE 5W-30 has been specifically developed for Mazda's and Mitsubishi's latest generation of diesel engine cars. It therefore ensures maximum service life of the diesel particle filter, as well as low wear, clean engine operation and long oil change intervals.

Specifications/Approvals:
ACEA C1

Recommendations:
Ford WSS M2C 934-B
JASO DL-1
Mazda
Mitsubishi

Content	PU	Part-No.
1 l	12	3189
5 l	4	3187
20 l	1	9472
60 l	1	9473
200 l	1	9474



megol Motorenoel Surface Protection SAE 5W-30

Modern low-viscosity engine oil for the latest generation of Ford vehicles. This low-viscosity, highly shear-resistant engine oil is sure to prevent deposit build-up, reduces friction loss in the engine and provides optimal wear protection. This leads to savings in fuel consumption while at the same time extending the life of the engine. megol Motorenoel Surface Protection SAE 5W-30 is backwards compatible, i.e. it can also be used in older Ford vehicles.

Specifications/Approvals:
ACEA A5/B5
Ford WSS-M2C 913-D
Jaguar / Land Rover STJLR.03.5003

Recommendations:
Ford WSS-M2C 913-A
Ford WSS-M2C 913-B
Ford WSS-M2C 913-C

Content	PU	Part-No.
1 l	12	3193
5 l	4	3192
20 l	1	9476
60 l	1	9477
200 l	1	9478



megol Motorenoel Efficiency SAE 5W-30

High-grade engine oil based on the low SAPS technology, which has been specially tailored to suit the final exhaust gas treatment systems of the latest generation diesel engines, it can be also used in gasoline engines. It therefore fulfils the highest performance requirements of these modern engines and ensures maximum service life of the diesel particle filter, as well as low wear, clean engine operation and long oil change intervals.

Specifications/Approvals:
ACEA C3
API SN/CF
BMW Longlife-04
MB-Approval 229.31, 229.51 and 229.52
VW 502 00/505 00/505 01
dexos2 APPROVED

Recommendations:
ACEA A3/B4
Ford WSS-M2C 917-A

Note: This product is only available in Europe.

Content	PU	Part-No.
1 l	12	3196
5 l	4	3194
20 l	1	9480
60 l	1	9481
200 l	1	9482



megol Motorenoel Super Leichtlauf DRIVER SAE 0W-40

Modern, fully synthetic low-friction motor oil for year-round use. Its combination of unconventional synthetic base oils with the advanced additive technology guarantees low viscosity and high shear resistance. This product reliably prevents the formation of deposits, reduces frictional losses in the engine and optimally protects against wear. Ensures savings in fuel and an extended service life of the engine. Recommended for gasoline and diesel engines, including those with a turbocharger and catalytic converter.

Specifications/Approvals:
ACEA A3
ACEA B4
API CF
API SM

Recommendations:
BMW Longlife-98
MB 229.3
Opel GM-LL-B-025
Porsche A40
VW 502 00/505 00

Content	PU	Part-No.
1 l	12	4894
4 l	4	9065
5 l	4	4895
20 l	1	4896
60 l	1	4897
200 l	1	4898



megol Motorenoel Low Emission SAE 5W-40

High-performance motor oil based on HC synthetic technology with a new special additive system (Low-SAPS Technology). Meets the high performance requirements and quality level of modern gasoline and diesel engines. In particular, it guarantees the effectiveness of the Euro 4/Euro 5 emission control systems over very long periods as well as low wear and good engine cleanliness. Particularly suitable for pump-jet engines (PD) from Volkswagen (VAG). Also for Ford Galaxy models with VAG PD engines.

Specifications/Approvals:
ACEA C3
API SN/CF
BMW Longlife-04
Ford WSS-M2C 917-A
MB-Approval 229.31
Porsche A40
VW 502 00/505 01

Recommendations:
ACEA A3/B4
dexos 2
Fiat 9.55535-S2
Renault RN 0700/ RN 0710

Content	PU	Part-No.
1 l	12	6573
1 l	12	9608 [1]
4 l	4	6675
5 l	4	6574
5 l	4	9610 [1]
20 l	1	6575
60 l	1	6576
200 l	1	6581



megol Motorenoel Ultra Performance Longlife SAE 5W-40

Modern low-friction motor oil based on HC synthetic oils. Its perfectly tailored combination of additives reliably prevents the formation of deposits, reduces frictional losses in the engine and optimally protects against wear. It therefore results in fuel savings and at the same time leads to a longer service life of the engine. Offering a wide range of applications, it is ideally suited for vehicles with gasoline and diesel engines (without diesel particulate filter) with and without turbocharging.

Specifications/Approvals:
ACEA A3
ACEA B3
ACEA B4
API CF
API SN
BMW Longlife-98
MB-Approval 229.3
Porsche A40
VW 502 00/505 00

Recommendations:
Fiat 9.55535-H2
Fiat 9.55535-M2

Content	PU	Part-No.
1 l	12	4361
4 l	4	6486
5 l	4	6328
5 l	4	9607 [1]
20 l	1	4359
60 l	1	4358
200 l	1	6398

[1] GB-F-E-P-NL-ARAB

ENGINE OILS FOR CARS



megol Motorenoel High Condition SAE 5W-40

Premium low-friction motor oil for year-round use. Developed for modern injection engines with and without turbocharger. Its combination of unconventional hydrocrack-based base oils with the very latest additive technology guarantees low viscosity and high shear resistance. The perfectly tailored formulation prevents deposits, lowers friction losses and provides optimum protection for the engine against wear. This delivers fuel savings while prolonging the life of the engine, among other benefits.

Specifications/Approvals:
ACEA A3/B4
API SN/CF
BMW Longlife-01
MB-Approval 229.5
Porsche A40
VW 502 00/505 00

Recommendations:
Fiat 9.55535-H2, M2
Opel GM LL-B-025
PSA B71 2294, 2296
Renault RN 0700
Renault RN 0710

Content	PU	Part-No.
1 l	12	3199
5 l	4	3198
20 l	1	9484
60 l	1	9485
200 l	1	9486



megol Motorenoel Syntech Premium SAE 10W-40

Premium low-friction motor oil. Its optimized combination of high-tech fluids, modern additive technology and synthetic components makes it suitable for year-round use in gasoline and diesel engines with and without turbocharging. It improves engine performance and reduces friction and wear. Ideal for use in older vehicles (youngtimers).

Specifications/Approvals:
ACEA A3/B4
API SN/CF
MB-Approval 229.1
VW 501 01/505 00

Recommendations:
PSA B71 2300

Content	PU	Part-No.
1 l	12	4339
1 l	12	9600 [1]
4 l	4	6475
5 l	4	4338
5 l	4	9601 [1]
20 l	1	4797
60 l	1	4798
200 l	1	4799
IBC 1000 l	1	6884



megol Motorenoel HD-C3 SAE 15W-40

High performance multigrade motor oil that is particularly suitable for economical year-round use as a universal oil in mixed vehicle fleets. Thanks to its carefully selected additive package combined with outstanding base oils, it can be used in modern high performance diesel engines as well as in gasoline engines. Meets the requirements of major diesel and gasoline engine manufacturers. The ideal lubricant for diesel and gasoline engines with and without catalytic converters, including those with exhaust gas turbochargers. Also recommended for older vehicles (youngtimers).

Specifications/Approvals:
ACEA A3/B4, E2
API SL/CF, CG-4
MAN M 3275-1
MB-Approval 228.3/229.1

Recommendations:
Allison C4
Caterpillar TO-2
Mack EO-L
MTU Typ 2
PSA B71 2295
Volvo VDS

Content	PU	Part-No.
1 l	12	4729
4 l	4	6478
5 l	4	4728
20 l	1	4727
60 l	1	4725
200 l	1	4716



megol Motorenoel Universal SAE 20W-50

A high performance multi-grade engine oil which is particularly suitable for use as an all-year oil in commercial vehicles. It meets the requirements of all main national and international petrol and diesel engine manufacturers. The ideal engine lubricant for petrol engines with and without catalytic converters and for diesel engines including turbo chargers, especially for the generation of EURO I to EURO III engines.

Specifications/Approvals:
ACEA A3/B4, E2
API SL/CG-4
Allison C4
Caterpillar TO-2
MIL-L-2104 E

Recommendations:
MAN 271
MB 228.3

Content	PU	Part-No.
1 l	12	4384
1 l	12	9628 [1]
4 l	4	9148
5 l	4	4381
20 l	1	6484
60 l	1	6863
200 l	1	6485

GEAR OILS FOR CARS



megol Hydraulikoel ATF Dexron II D

Hydraulic fluid for automatic transmissions and hydraulic clutches which require a Dexron D type automatic transmission fluid. Guarantees perfect functioning of the fluid transmissions even under the most strenuous operating conditions and large temperature fluctuations. Also suitable for systems functioning under strenuous operating conditions.

Specifications/Approvals:
Allison C4; Caterpillar TO-2; Citroen; Denison; Dexron II D; MAN 339 Typ L1/V1/Z1; MB-Approval 236.6, ZF TE-ML 03D, 04D, 11A, 14A, 17C

Recommendations:
Audi
Ford Mercon M2C 166-H
GM-Dexron
Voith H55.6335.XX (G 607)
ZF TE-ML 09

Content	PU	Part-No.
1 l	6	6479
20 l	1	4879
60 l	1	4877
200 l	1	4861



megol Transmission-Fluid ATF III

Hydraulic fluid for automatic gear boxes and hydraulic clutches, which require a Dexron III type automatic transmission fluid. Guarantees perfect functioning of the fluid transmissions even under the most strenuous operating conditions and large temperature fluctuations. Also suitable for systems functioning under strenuous operating conditions.

Specifications/Approvals:
Allison C4; Allison TES 389; Caterpillar TO-2; Dexron II D; Dexron II E; Dexron III G; Dexron III H; MAN 339 Typ L1/V1/Z1; MB-Approval 236.1; TASA; Voith H55.6335.xx; ZF-TE-ML 04D, 14A, 17C

Recommendations:
Ford Mercon
MB 236.6
Volvo 97341
ZF TE-ML 02F, 03D, 09, 11A, 11B, 14B

Content	PU	Part-No.
1 l	6	4875
1 l	6	9638 [1]
5 l	4	6477
20 l	1	4876
60 l	1	4659
200 l	1	4862

[1] GB-F-E-P-NL-ARAB



megol Getriebeoel ATF Smooth

Automatic transmission oil based on high quality synthetic base oils combined with the latest additive technology to meet the requirements on the new generation of Mercedes-Benz NAT 2 passenger car automatic transmissions up to 7-speed automatic. Megol Getriebeoel ATF Smooth is an excellent problem solver with shifting problems.

Recommendations:
MB 236.12
MB 236.14

Content	PU	Part-No.
1 l	6	9424
20 l	1	3168
200 l	1	2470



megol Getriebeoel ATF Variable

One of the latest generation automatic gearbox oils, based on HC synthesis base oils combined with the most modern, efficient additives. It meets the demands of several manufacturers of automatic transmissions and vehicles around the world. megol Getriebeoel ATF Variable is suitable for use in automatic transmissions, manual transmissions, clutch and steering systems, hydraulic systems and auxiliary drives, both in passenger cars and commercial vehicles.

Recommendations:
BMW 7045 E/8072 B/LA 2634/LT 71141; Chrysler ATF +3/ATF +4; Daimler NAG-1; JWS 3309 (Aisin Warner); MAN 339 Typ V1/Typ Z2/Typ Z1; MB 236.2/236.3/2 36.5/236.6/236.7/236.9/236.10/236 .11; Subaru ATF; Volvo 97340/97341; Voith H55.6335.XX (G 607); VW G 052 990/055 025; ZF TE-ML 02F/03D/04D/ 05L/09/11A/11B/14A/14B/17C; Toyota Type T-IV/T-III; Dexron III H; Mitsubishi SP-II/SP-III; Mazda ATF M-V/M-III; Nissan AT-Matic J Fluid/D Fluid/K Fluid; AE (LT 71141); Kia SP-II/SP-III; Hyundai SP-II/ SP-III; Ford Mercon V; Allison C4/TES 295; JASO 1-A; Caterpillar TO-2; Honda ATF Z1

Content	PU	Part-No.
1 l	6	9427
20 l	1	3171
200 l	1	9008



megol CVT Dynamik

High-performance automatic gearbox oil specially formulated to be used in the new CVT transmission generation. The basis of selected base oils and special additives offers the best possible protection against foaming, necessary in CVT transmissions. It also features a good ageing and oxidation stability. megol CVT Dynamik is tried and tested, especially in the Autotronic transmissions used in Mercedes A and B classes, and also in many different manufacturers' continuously variable automatic transmissions (among others also Audi Multitronic).

Recommendations:
Ford CVT23, CVT30/MERCON C; Honda HMMF; Jeep NS-2/CVTF+4; MB 236.20; Mini Cooper (EZL 7/99); Mitsubishi CVTF-J1/CVTF-J4; Nissan CVT NS-2 Fluid; Subaru NS-2; Suzuki CVT Green1/NS-2/ TC; Toyota TC; Subaru Lineartronic CVTF; VW G 052 180/G 052 516; Dodge NS-2/CVTF+4; GM/Saturn DEX-CVT

Content	PU	Part-No.
1 l	6	9452
20 l	1	3172



megol Doppelkupplungsgetriebe Fluid

megol Dual Clutch Transmission Fluid is a high-performance gear oil which has been specially developed for the dual clutch transmissions used by the VW Group (i.e. in VW, Audi, Skoda and Seat vehicles). Only top quality HC synthetic base oils are used for the fluid in combination with an exclusive additive technology. This consistently guarantees stable friction characteristics, even under extreme conditions. Under no circumstances should this oil be mixed with other dual clutch oils.

Recommendations:
Chrysler; Ford WSS-M2C 936-A; VW G 052 182, G 052 529; Mitsubishi Dia Queen; Volvo 1161839, 1161838; BMW 83 22 2 148 579; BMW 83 22 2 147 477; BMW 83 22 2 148 578; BMW 83 22 0 440 214; Peugeot Citroen (PSA) 9734.S2; MB 236.21; Porsche 999.917.080.00

Content	PU	Part-No.
1 l	6	3529



megol Mehrzweckgetriebeoel GL 4 SAE 85W-90

High-grade gearbox oil with a wide range of uses for high tooth flank stresses. Gearbox oils of this type are recommended by motor vehicle and gearbox manufacturers for use in synchronised and nonsynchronised manual gearboxes, power units for building machinery, agricultural machinery and tractors.

Specifications/Approvals:
API GL4
ZF TE-ML 17A
ZF TE-ML 16A
ZF TE-ML 19A

Recommendations:
MIL-L 2105
MAN 341 Typ E1
MAN 341 Typ Z2

Content	PU	Part-No.
20 l	1	4888
60 l	1	4889
200 l	1	4890



megol Mehrzweckgetriebeoel GL 4 SAE 80W-90

High-grade gearbox oil with a wide range of uses for high tooth flank stresses. Gearbox oils of this type are recommended by motor vehicle and gearbox manufacturers for use in synchronised and nonsynchronised manual gearboxes, power units for building machinery, agricultural machinery and tractors.

Specifications/Approvals:
API GL 4

Recommendations:
MAN 341 Z1
MIL-L-2105

Content	PU	Part-No.
1 l	6	4866
20 l	1	4821
60 l	1	4822
200 l	1	4823

GEAR OILS FOR CARS



megol Hypoid-Getriebeoel GL 4 „+" SAE 75W-90

Fully synthetic multi-grade gearbox oil with anti-corrosion and high pressure properties for low and high temperatures. Reduction of friction helps reduce fuel consumption. Multi-purpose gearbox oil with a wide range of uses in vehicle gearboxes, in particular manual transmissions. At low temperatures it eliminates gear shifting problems and noise development in manual transmissions. As a result of its fully synthetic base oils, together with modern additive technology, this lubricant guarantees outstanding wear protection in all operating conditions in both summer and winter, and is even suitable for Arctic conditions.

Specifications/Approvals:
API GL 4 „+"

Recommendations:
Ford ESD M2C 175-A
VW 501 50 (G 50)
ZF TE-ML 08A
MIL-L 2105

Content	PU	Part-No.
1 l	6	3535
20 l	1	8616
60 l	1	6668
200 l	1	8618



megol Spezial MTF GL 5 SAE 75W-80

Specially developed gearbox oil which is particularly notable for the fact that it means that gearshifts in the gearbox can be completed easily and precisely even in low temperatures and with a high load. This product was specially developed for Peugeot and Citroën manual transmissions and can also be used for solving problems relating to noise build-up and gearshift difficulties for gearboxes from other manufacturers.

Specifications/Approvals:
API GL 5

Recommendations:
MIL-L-2105 C
PSA

Content	PU	Part-No.
1 l	6	9435
20 l	1	9437
60 l	1	9438



megol Hypoid-Getriebeoel GL 5 SAE 75W-90 (semi- synthetic)

Partly synthetic multi-grade gearbox oil with anti-corrosion and ultra-high pressure properties providing optimum lubrication at low and high temperatures. Reduction of friction helps reduce fuel consumption. Used in vehicle axle transmissions and for common lubrication of change gearboxes and differentials enclosed in a single casing. At low temperatures it eliminates gear shifting problems and noise development in manual transmissions.

Specifications/Approvals:
API GL 5

Recommendations:
MIL-L-2105 D

Content	PU	Part-No.
20 l	1	8623
60 l	1	8624
200 l	1	8625



megol Hypoid-Getriebeoel GL 5 SAE 75W-140 LS

Fully synthetic gearbox oil with LS-additive (LS = limited slip) for use in motor vehicles, preferably BMW's with locked axle systems and in axles, manual gearboxes and auxiliary drives with extended oil-change intervals in commercial vehicles. Megol Hypoid-Getriebeoel GL 5 SAE 75W-140 LS is suited for a wide temperature range because of the adjusted SAE-class.

Specifications/Approvals:
API GL 5
VME

Recommendations:
BMW real-axel tranmission oil
Ford WSL-M2C 192-A
Scania STO 1:0
ZF TE-ML 05D / 12D / 16G

Content	PU	Part-No.
1 l	6	3536

CENTRAL HYDRAULIC OIL



megol Zentralhydraulikoel

megol Zentralhydraulikoel is a special, synthetic and mineral oil-based hydraulic oil with ash-free additives to improve its viscosity, coefficient of friction, wear protection, oxidation protection, foaming and corrosion protection properties. megol Zentralhydraulikoel offers an ideal capacity for use as a central hydraulic oil in power steering and level control systems, hydraulic brake boosters and hydro-pneumatic suspension systems. megol Zentralhydraulik - oel's special formulation guarantees an excellent cold behaviour and is therefore particularly suited for use in cold countries.

Specifications/Approvals:
MAN 3289

Recommendations:
BMW 81229407758
Ford WSS-M2C 204-A
MB 345.0
Opel 1940 766
VW G 004 000
VW G 002 000
ZF TE-ML 02K

Content	PU	Part-No.
1 l	6	6304
20 l	1	8641
60 l	1	8642

SERVICE PRODUCTS



Meguin Bremsenreiniger

Universal cleaner for rapid cleansing and degreasing of small components in vehicle and industrial engineering. For brakes, clutches, transmissions, and for use in fitting and repair work. Removes oil and grease spots from floor coverings, materials and linings.

Content	PU	Part-No.
500 ml	12	8483
5 l	1	4819
20 l	1	4892
60 l	1	4820

Note: The instructions issued by the vehicle manufacturers are to be followed.